



TOLERANCES UNLESS OTHERWISE SPECIFIED		ROUGHNESS		EXTERNAL FORM		SIZE		MATERIAL		REMARKS	
Ø75mm6	+0.030	TO	SYMBOLS	NO.	DESCRIPTIONS	DATE	DESIGNED	CHECKED	APPROVED		
Ø130mm6	+0.040	TO	SYMBOLS	NO.	DESCRIPTIONS	DATE	DESIGNED	CHECKED	APPROVED		
Ø130mm6	+0.015	TO	SYMBOLS	NO.	DESCRIPTIONS	DATE	DESIGNED	CHECKED	APPROVED		
16° 66°	±0.2	0.08	0.08	1	90KW 4P 1/5~1/20	2008.12.03	J.R.H				
86° 125°	±0.4	0.08	0.08	2	JK-BC 2300 REDUCER	2008.12.03	J.R.H				
125° 250°	±0.5	0.08	0.08	3	JK-BC 2300 REDUCER	2008.12.03	J.R.H				
250° 500°	±0.6	0.08	0.08	4	JK-BC 2300 REDUCER	2008.12.03	J.R.H				
500° 1000°	±0.8	0.08	0.08	5	JK-BC 2300 REDUCER	2008.12.03	J.R.H				
1000° 2000°	±1.0	0.08	0.08	6	JK-BC 2300 REDUCER	2008.12.03	J.R.H				
2000° 4000°	±1.5	0.08	0.08	7	JK-BC 2300 REDUCER	2008.12.03	J.R.H				
ANGLE	±0.5	0.08	0.08	8	JK-BC 2300 REDUCER	2008.12.03	J.R.H				

JEIL ENGINEERING & INDUSTRIAL CO., LTD.